

- 1.4 inch exit Neodymium compression driver
- Very fast impulse response for excellent transient reproduction
- Natural Sound frequency response extended up to 20 kHz
- 240 W program power handling
- 112 dB 1W / 1mt sensitivity
- 75 mm (3 in) Edgewound CCAW voice coil
- Glass-PEN dome with proprietary suspension geometry
- Next gen 4-slot metal alloy phase plug design
- Copper sleeve for reduced distortion and increased high end output

The ND3SG 1.4 inch exit neodymium high frequency compression driver represents the last addition to the natural sound compression drivers family.

For the first time a Glass dome sandwiched to a proprietary treated PEN (polyethylene naftalate) suspension, has been used to produce a pro audio high frequency component.



The composite diaphragm assembly is made by a Glass dome strongly joined to the PEN suspension, in order to assure unmatched transient response, minimizing spurious resonances at very high frequencies. A bended former edge-wound aluminum 75mm voice coil completes the diaphragm assembly.

The ND3G moving assembly design assures extended frequency energy transfer for improved response linearity and unparallel reliability. This feature facilitates proper motion control of the dome in real working conditions. A proprietary treated Nomex former is used as Nomex shows a 30% higher value of tensile elongation at a working operative temperature (200°C) when compared to Kapton. Moreover, this proprietary former material is also suitable for use in higher moisture content environments.

The diaphragm kit self centering design allows high precision mounting and at the same time makes very easy the servicing procedure.

Despite of its compact size, the ND3SG neodymium magnet assembly has been designed to obtain 21KGauss in the gap for major benefits in transient response. The motor structure, throughout the precisely coherent metal alloy phase plug with 4 circumferential slots and copper ring on the pole piece, reduces inductance effect and distortion.

The ability to perform properly under inclement weather conditions is a key point of the Eighteen Sound philosophy. Hence, a special treatment is applied to the magnet and the top and back plates of the magnetic structure in order to make the driver more resistant to the corrosive effects of salts and oxidization. This treatment is more effective than any other coating commonly used.





## ND3SG 8Ω

### HF Drivers - 1.4 Inches

#### SPECIFICATIONS<sup>1</sup>

|                                        |                |
|----------------------------------------|----------------|
| Throat Diameter                        | 36 mm (1.4 in) |
| Nominal Impedance                      | 8 Ω            |
| Minimum Impedance                      | 6.6 Ω          |
| Nominal Power Handling <sup>2</sup>    | 120 W          |
| Continuous Power Handling <sup>3</sup> | 240 W          |
| Sensitivity <sup>4</sup>               | 112.0 dB       |
| Frequency Range                        | 0.8 - 20.0 kHz |
| Recommended Crossover <sup>5</sup>     | 1.2 kHz        |
| Voice Coil Diameter                    | 75 mm (3.0 in) |
| Winding Material                       | Aluminum       |
| Diaphragm Material                     | Glass          |
| Flux Density                           | 2.1 T          |
| Magnet Material                        | Neodymium      |

#### MOUNTING AND SHIPPING INFO

|                  |                                   |
|------------------|-----------------------------------|
| Overall Diameter | 120 mm (4.72 in)                  |
| Depth            | 53 mm (2.09 in)                   |
| Net Weight       | 2.3 kg (5.07 lb)                  |
| Shipping Box     | 165x150x65 mm (6.50x5.91x2.56 in) |

1. Driver mounted on Eighteen Sound XR1464C horn
2. 2 hour test made with continuous pink noise signal within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated nominal impedance.
3. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.
4. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
5. 12 dB/oct. or higher slope high-pass filter.